

# **-1/-2 HYDRAULIC CYLINDERS**

ACCEPTED VENDORS:  
BAILEY HYDRAULICS  
2527 WESTCOTT BLVD.  
KNOXVILLE, TN. 37931  
800-800-1810

OPERATING PRESSURE: 3000psi.  
FINISH: GLOSS BLACK PAINT.

REVISION HISTORY					
DATE	REV	DESCRIPTION	AUTHOR	CHECKED BY	APPROVED
08/08/17	A	INITIAL RELEASE	EW	LS	JT
10/4/17	B	ADDED -2	EW	LS	JT
7/16/19	C	ADDED -3	CMK	LS	CMK




TABLE					
DASH #	MANUFACTURER PART NO.	STROKE	BODY LENGTH "X"	COMPRESSED LENGTH "Y"	EXTENDED LENGTH "Z"
-1	400-502	8	14	14	22
-2	400-504	12	16	18	30

## **-2 CYLINDER SHOWN**

### NOTE:

This drawing defines the overall geometry and performance specifications of the part/assembly, and constitutes the acceptance criteria thereof. Only the item(s) described in this document procured from the vendor and/or manufacturer listed hereon are approved for use. A substitute item shall not be used without prior approval. Conformance of hardware to these requirements is acceptable in lieu of vendor and/or manufacturer documentation.

CONFORMITY DECLARATION  
THE INFORMATION AND DATA CONTAINED HEREIN IS  
PROPERTY AND IS CONTROLLED BY CONFIDENTIAL, AND  
SHALL NOT BE DISCLOSED, REPRODUCED OR OTHERWISE  
TRANSMITTED WITHOUT THE EXPRESS WRITTEN  
PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO

<b>Paravion<sup>®</sup> Technology Inc.</b>		TITLE HYDRAULIC CYLINDER		DRAWING NUMBER ES39212	
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = $\pm .1$ .XX = $\pm .05$ .XXX = $\pm .010$ ANGLES = $\pm 1^\circ$		DRAWN BY EW	CHK'D BY LS	APPR'D. BY JT	DATE 8/8/17
THREADS: INTERNAL: CLASS 2B EXTERNAL: CLASS 2A		3RD ANGLE PROJECTION		DO NOT SCALE DRAWING ©2017 PARAVION TECH. INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY INC.	
				REV C	ECO
				SHEET 1 OF 2	



# -3 HYDRAULIC CYLINDER

ACCEPTED VENDORS:  
MOTION FLOW CONTROL PRODUCTS, INC.  
834 S.E. FRONTAGE ROAD  
FORT COLLINS, CO 80524  
970.221.8008

MANUFACTURER:  
PARKER HANNIFIN CORP.  
CYLINDER DIVISION  
DES PLAINES, IL 60016

## NOTES

1. MFG P/N: 1.50SBRDH8T419A12.000
2. BORE: 1.5 IN
3. STROKE: 12.0 IN
4. NOMINAL PRESSURE: 3000 PSI
5. SEALS: LOW TEMPERATURE (CLASS 4), -45°C (-50°F) TO 65°C (150°F) WITH ROD WIPER
6. MATERIALS: BODY - CARBON STEEL  
ROD - CARBON STEEL, CASE HARDENED AND HARD CHROME PLATED  
HEAD - DUCTILE IRON  
PISTON - DUCTILE IRON
6. FINISH: GLOSS BLACK ENAMEL



## NOTE:

This drawing defines the overall geometry and performance specifications of the part/assembly, and constitutes the acceptance criteria thereof. Only the item(s) described in this document procured from the vendor and/or manufacturer listed hereon are approved for use. A substitute item shall not be used without prior approval. Conformance of hardware to these requirements is acceptable in lieu of vendor and/or manufacturer documentation.

CONFORMANCE NOTATION:  
THE INFORMATION AND DATA CONTAINED HEREIN IS  
PROVISIONAL AND IS SUBJECT TO CHANGE WITHOUT  
NOTICE. THIS DRAWING IS THE PROPERTY OF PARAVIOR  
TECHNOLOGY, INC. AND IS NOT TO BE REPRODUCED OR  
TRANSMITTED IN ANY FORM OR BY ANY MEANS  
WITHOUT THE WRITTEN PERMISSION OF PARAVIOR TECHNOLOGY, INC.

PROTO

Paravior <sup>®</sup> Technology Inc.		TITLE		DRAWING NUMBER	
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED:		HYDRAULIC CYLINDER		ES39212	
DRAWN BY EW	CHK'D BY LS	APRVD. BY JT	DATE 8/8/17	REV C	ECO
DO NOT SCALE DRAWING				SHEET	
THREADS: INTERNAL CLASS 2B EXTERNAL CLASS 2A				2 OF 2	
3RD ANGLE PROJECTION					